# **TECHNICAL DATA**







Adhesives

# **QS 900**

## **QUICK STICK ADHESIVE**

Spray Adhesive QS 900 is a fast tacking, non-chlorinated spray adhesive. This specialist formulation will provide instant 'grab', which allows pressure to be exerted on the bond before full cure strength is achieved.

Spray Adhesive QS 900 provides permanent bonds and it is free from chlorinated solvents. Tack time approximately 30 seconds. Economical in use - only a light film is required for instant grab.

#### **PRODUCT CODES / FILL SIZES**



31626 / 500ml

#### **APPLICATIONS**

QS 900 Quick Stick Adhesive has been formulated to satisfy the demands of the carpeting and flooring trade. It is also suitable for bonding many different substrates, including:

- Carpet
- Underlay
- Foam
- Fabric
- Cork

- Upholstery
- Paper, Cardboard
- Wood
- To a wide variety of different surfaces

### **DIRECTIONS**

- Apply a light, fine even coating to both surfaces to be bonded from 9" - 12" (25 - 30 cm).
- Wait until the adhesive is tack-dry and bond the surfaces together using firm pressure. Heavier applications of QS 900 may prolong the tack time.
- To prevent blockages, invert the can after use and spray to clear the nozzle.

# **TECHNICAL DATA**



#### **TECHNICAL DATA (WITHOUT PROPELLANT)**

Appearance	Clear, amber liquid
Odour	Characteristic Solvent
SG @ 25°C	0.66
Pressure @ 25°C	4 Bar
Discharge rate	1.2 g/sec
Polymer type	Styrene Butadiene Rubber
Tack time	Approximately 30 seconds
Bonding time	Maximum adhesion in 12/24 hours
Temperature range	Up to 50°C (dried film)
Solubility	Soluble in some solvents, insoluble in water
Recommended solvents	Amberklene FE10, ME20
Flammability	Classified as extremely flammable under CHIP Regulations

### **MATERIALS COMPATIBILITY**

OK -

CAUTION May affect certain plastics. Always test a small, inconspicuous area before general use

NOT OK -

#### **STORAGE & SHELF LIFE**

The product may be stored at normal ambient temperatures and has a shelf life of not less than 3 years with correct storage. Aerosols should always be stored below 50°C, away from direct heat and naked flame.

#### **HEALTH AND SAFETY**

A separate Safety Data Sheet (SDS) according to EC Regulation 73/404/EEC and 648/2004/EC is available from Ambersil.com or via info.uk@crcind.com

# MISREPRESENTATION ACT 1967

#### **TRADE DESCRIPTIONS ACT 1968**

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

Version 3.1 Created: July 2019 Updated: October 2020

CRC Industries UK Ltd. Wylds Road,Bridgwater Somerset, TA6 4DD United Kingdom

Company Registered No. 04910479

t +44 (0)1278 727200

**f** +44 (0)1278 425644

e sales.uk@crcind.com
w www.ambersil.com

w www.ambersii.com

VAT No. GB 821 5195 42



